

## PC requirements

- Windows 10 or higher
- Browser: Edge, Chrome or Brave

## 1 - Insert the MDB Connect

- ▶ Making sure that your automatic coffee machine is **switched off**, insert the MDB Connect into the service socket.



- ▶ Switch on the automatic coffee machine.
- ▶ Open the bracket for the MDB interface system 2.0.
- ▶ Insert the second MDB Connect and close the bracket again.



## 2 - Prepare the MDB interface system

- ▶ Connect your computer to the JURA MDB interface system 2.0 using a USB-C cable\*. Do **not** connect the power supply unit!

The LED of the MDB interface system 2.0 lights up green.

The LED of the MDB Connect inserted in the interface flashes blue.

### Info

Make sure that your USB-C cable can not only charge, but also transfer data.

\*The USB-C cable is not supplied as standard.

### 3 - Connect the MDB interface system (EVIS website)

- ▶ Launch the browser-based app for configuration of the MDB interface system 2.0 using the following link: <https://mineralis.evis.ch/>
- ▶ Click on the three lines in the top right-hand corner to select your preferred language.
- ▶ Click on «**Connect device**».
- ▶ Connect with “**EVIS**”.  
«**Device connected**» appears on the screen of your computer.
- ▶ Click on “**Parameter Editor**”.

### 4 - Carry out the configuration (EVIS website)

- ▶ Carry out the configuration in accordance with the table below:

Title	Value	Value example	Description
Device name		ACM Hall 1	Name for your automatic coffee machine
Host protocol	JURA		JURA is shown automatically
Text credit		Credit	Enter text to be shown in the display Examples: Kredit, Credit, Guthaben
Text price		Price	Enter text to be shown in the display Examples: Preis, Price, Zu bezahlen
Text locked		Locked	Enter text to be shown in the display Examples: Gesperrt, locked, blockiert
Product prices symbol currency		Text	TEXT or select currency symbol from the drop-down menu
Product prices text currency		CHF	Enter text to be shown in the display Examples: CHF, EUR
Device settings pin code		123456	Pin code for access to the machine settings
Maintenance settings pin code		654321	Pin code for access to the maintenance settings
Automatic debt collection timeout		ON	During the timeout, a check is carried out to verify whether there is sufficient credit available.
View product prices		ON	If set to 0, there will be no product name or product price shown on the machine display.
Product pricing format		0	0 = 1.10 CHF (space between amount and currency) 1 = 1.10CHF (no space between amount and currency) 2 = CHF 1.10 (currency before amount with space) 3 = CHF1.10 (currency before amount without space)
Send prices		ON	Prices are sent to the automatic coffee machine every time the MDB interface system 2.0 is started.
Display time for price/text		3.0	If there is no credit available, the product price is shown in the machine's display for 3 seconds.
Polltime		2.0	Time interval for information requests between MDB interface system 2.0 and ACM (MDB Connect).

Title	Value	Value example	Description
Communication timeout		5.0	MDB interface system 2.0 waits 5 seconds, for example, until the next request is sent should the ACM (MDB Connect) fail to send a signal.
EMC test mode		OFF	Used for EMC testing. Not required for daily use.
Reset MDB Connect		OFF	MDB Connect will be reset when it is next started
MDB Connect version			Read out automatically, software version
Operating mode		All media must be ready	Payment systems have various start times. The ACM can either be operated when one system or when all systems are ready.
MDB coin validator		OFF	
External MDB device 1		ON	
External MDB device 2		OFF	
Activate rebooking		OFF	

## 5 - Send configuration (EVIS website)

- ▶ Click on **“Send configuration”**.  
“Configuration sent” appears on the screen of your computer.

## 6 - Connect automatic coffee machine with MDB

- ▶ Access the machine settings of your automatic coffee machine.
- ▶ Select the sub-menu **“Accessories”**.
- ▶ Select **“Incasso”**.  
Make sure the MDB Connect is positioned in close proximity to the automatic coffee machine (max. distance of 0.5 m).
- ▶ Select **“Connect”**.  
“Connected” appears on the display of your automatic coffee machine.

## 7 - Enter product prices (EVIS website)

- ▶ Click on **“Product and Price Editor”**.
- ▶ Click on **“Read products”**.
- ▶ Enter a price for each item.
- ▶ Click on **“Send products”**.
- ▶ Click on **“Restart device”**.

### Info

Empty = Product is not displayed  
00 = Product without price

## 7 - Finishing up

- ▶ Remove the USB-C cable from the computer and the JURA MDB interface system 2.0.
- ▶ Connect the preferred accounting system at the MDB connector.



- ▶ Connect the power adapter to the MDB interface system 2.0.



- ▶ Connect the mains cable to the power adapter.



- ▶ Insert the mains plug into a socket.

Make sure the MDB Connect is positioned in close proximity to the automatic coffee machine (max. distance of 0.5 m).

The JURA MDB interface system 2.0 will now automatically reconnect with the configured automatic coffee machine.